

AUXILIARY PARTS-STANDARD METAL SHIMS FOR CONE ADJUSTED
BEARINGS

Numéro d'article:	Shims		Cap Screws				
	Thickness(mm/in.)	Shaft Size(mm/in.)	No.	Size(mm/in.)	d ₁ (mm/in.)	d ₂ (mm/in.)	d ₃ (mm/in.)
T50605	0.13	63.5 to 73.2	3	12.7	35.1	60.5	14.2
T50605	0.005	2.50 to 2.88	3	0.5	1.38	2.38	0.56
T50606	0.18	63.5 to 73.2	3	12.7	35.1	60.5	14.2
T50606	0.007	2.50 to 2.88	3	0.5	1.38	2.38	0.56
T50607	0.51	63.5 to 73.2	3	12.7	35.1	60.5	14.2
T50607	0.02	2.50 to 2.88	3	0.5	1.38	2.38	0.56
T50608	0.13	76.2 to 85.9	3	12.7	44.4	73.2	14.2
T50608	0.005	3.00 to 3.38	3	0.5	1.75	2.88	0.56
T50609	0.18	76.2 to 85.9	3	12.7	44.4	73.2	14.2
T50609	0.007	3.00 to 3.38	3	0.5	1.75	2.88	0.56
T50610	0.51	76.2 to 85.9	3	12.7	44.4	73.2	14.2
T50610	0.02	3.00 to 3.38	3	0.5	1.75	2.88	0.56
T50611	0.13	88.9 to 104.6	3	12.7	57.2	85.9	14.2
T50611	0.005	3.50 to 4.12	3	0.5	2.25	3.38	0.56
T50612	0.18	88.9 to 104.6	3	12.7	57.2	85.9	14.2
T50612	0.007	3.50 to 4.12	3	0.5	2.25	3.38	0.56
T50613	0.51	88.9 to 104.6	3	12.7	57.2	85.9	14.2
T50613	0.02	3.50 to 4.12	3	0.5	2.25	3.38	0.56
T45882	0.13	108 to 117.3	3	15.7	76.2	103.1	17.5
T45882	0.005	4.25 to 4.62	3	0.62	3	4.06	0.69
T50633	0.18	108 to 117.3	3	15.7	76.2	103.1	17.5
T50633	0.007	4.25 to 4.62	3	0.62	3	4.06	0.69
T45884	0.51	108 to 117.3	3	15.7	76.2	103.1	17.5
T45884	0.02	4.25 to 4.62	3	0.62	3	4.06	0.69
T45885	0.13	120.6 to 124	3	15.7	88.9	117.3	17.5
T45885	0.005	4.75 to 4.88	3	0.62	3.5	4.62	0.69

AUXILIARY PARTS-STANDARD METAL SHIMS FOR CONE ADJUSTED

		BEARINGS					
T50634	0.18	120.6 to 124	3	15.7	88.9	117.3	17.5
T50634	0.007	4.75 to 4.88	3	0.62	3.5	4.62	0.69
T45887	0.51	120.6 to 124	3	15.7	88.9	117.3	17.5
T45887	0.02	4.75 to 4.88	3	0.62	3.5	4.62	0.69